

Essential

HETEROGENEOUS VINYL

For
unconditional
comfort

Essential

TECHNICAL DATA	STANDARD	TAPIFLEX ESSENTIAL 50	TAPIFLEX TILES 50	TAPIFLEX PLANKS 50	ACCZENT ESSENTIAL 70
CLASSIFICATION					
Classification	EN 651	Heterogeneous Acoustic floor covering based on polyvinyl chloride	Heterogeneous Acoustic floor covering based on polyvinyl chloride	Heterogeneous Acoustic floor covering – based on polyvinyl chloride	
	EN ISO 10582	–	–	–	Heterogeneous Compact floor covering based on polyvinyl chloride
	EN ISO 10874	33-42	33-42	33-42	34-43
Wear group	EN 651	T	T	T	–
Wear layer binder content	EN ISO 10582	–	–	–	Type I
TECHNICAL CHARACTERISTICS					
Total thickness	EN ISO 24346	3.30 mm	3.30 mm	3.30 mm	2.00 mm
Total weight	EN ISO 23997	2770 g/m²	3212 g/m²	3212 g/m²	3069 g/m²
Wear layer thickness	EN ISO 24340	0.50 mm	0.50 mm	0.50 mm	0.70 mm
Form of delivery	EN ISO 24341 (rolls)	Approx. 23 running metres x 200 cm	–	–	Approx. 23 running metres x 200 cm
	EN ISO 24342 (tiles)	–	50 x 50 cm - 20 tiles/box = 5 sqm	–	–
	EN ISO 24342 (planks)	–	–	100 x 25 cm - 20 planks/box = 5 sqm	–
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)					
Declaration of Performance	EN 14041	0120-0057-DoP-2014-05	0120-0061-DoP-2014-05	0120-0061-DoP-2014-05	0120-079-DoP-2019-02
Reaction to fire	EN 13501-1	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) Cfl-s1 glued over any derivate wood substrate	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) Cfl-s1 glued over any derivate wood substrate	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) Cfl-s1 glued over any derivate wood substrate	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) Bfl-s1 glued over any derivate wood substrate
Electrostatic properties	EN 1815	≤ 2.0 kV	≤ 2.0 kV	≤ 2.0 kV	≤ 2.0 kV
Thermal resistance	EN ISO 10456	0.04 m² K/W	0.04 m² K/W	0.04 m² K/W	0.02 m² K/W
Slip resistance	EN 13893	≥ 0.3	≥ 0.3	≥ 0.3	≥ 0.3
TECHNICAL PERFORMANCES					
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.20 mm Best measured value*: 0.10 mm Average measured value*: 0.12 mm	Required value: ≤ 0.20 mm Best measured value*: 0.10 mm Average measured value*: 0.12 mm	Required value: ≤ 0.20 mm Best measured value*: 0.10 mm Average measured value*: 0.12 mm	Required value: ≤ 0.10 mm Best measured value*: 0.02 mm Average measured value*: 0.03 mm
Impact sound reduction	NF EN ISO 717 / 2	ΔL _w = 20 dB	ΔL _w = 19 dB	ΔL _w = 19 dB	ΔL _w = 3 dB
Acoustical improvement	NF S31-074	L _{n,e,w} < 65 dB - Class A	L _{n,e,w} < 65 dB - Class A	L _{n,e,w} < 65 dB - Class A	L _{n,e,w} < 85 dB - Class C
Slip resistance ⁽¹⁾	DIN 51130	R9/R10 (Citizen Oak)	R9	R10 (Citizen Oak)	R9/R10 (Citizen Oak)
Furniture leg	EN 424	No damage	No damage	No damage	No damage
Castor chair	ISO 4918	No damage	No damage	No damage	No damage
Curl resultant to heat	EN ISO 23999	≤ 8 mm	≤ 2 mm	≤ 2 mm	≤ 8 mm
Light fastness	EN ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6
Dimensional stability	EN ISO 23999	≤ 0.10%	≤ 0.10%	≤ 0.10%	≤ 0.10%
Chemical resistance	EN ISO 26987	Not affected	Not affected	Not affected	Not affected
Underfloor heating		Suitable (maximum 27°C)	Suitable (maximum 27°C)	Suitable (maximum 27°C)	Suitable (maximum 27°C)
ENVIRONMENTAL PERFORMANCES					
Total VOC emissions	ISO 16000-9	≤ 10 µg/m³ (after 28 days)	≤ 10 µg/m³ (after 28 days)	≤ 10 µg/m³ (after 28 days)	≤ 10 µg/m³ (after 28 days)
COLOURS					
		38	6	3	7
The above information is subject to modification for the benefit of further improvement. (04/23).					
Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.					
    					

Colour code	NCS	Welding Rod	Corresponding skirting KS61	Colour code	NCS	Welding Rod	Corresponding skirting KS61	Colour code	NCS	Welding Rod	Corresponding skirting KS61	Colour code	NCS	Welding Rod	Corresponding skirting KS61	Colour code	NCS	Welding Rod	Corresponding skirting KS61	Colour code	NCS	Welding Rod	Corresponding skirting KS61
25094 002	S 4000-N	1287 483	206009 008	25094 205	S 2005-Y20R	1287 848	206009 013	25094 215	S 2002-Y50R	1292 455	1411 053	25094 223	S 2005-Y80R	1292 770	1411 053	25094 236	S 2002-Y50R	1292 770	206009 010	25190 000	S 5005-Y20R	1287 537	206009 013
25094 005	S 3005-Y50R	1287 291	206009 013	25094 207	S 1060-Y70R	1288 337	1411 047	25094 216	S 3502-Y	1292 771	1411 053	25094 224	S 4010-R70B	1287 740	1411 053	25094 301	S 6000-N	1287 482	206009 007	25190 001	S 4010-Y30R	1287 373	206009 013
25094 200	S 4040-R80B	1291 354	206009 030	25094 208	S 5010-B70G	1287 223	1411 056	25094 217	S 2030-G70Y	1287 494	1411 036	25094 225	S 3502-Y	1287 027	1411 053	25188 228	S 4020-Y30R	1292 373	206009 018	25190 100	S 3005-Y20R	1287 178	206009 013
25094 201	S 6500-N	1287 836	206009 006	25094 211	S 2040-B30G	1411044	206009 026	25094 218	S 3020-B30G	1287 762	206009 026	25094 226	S 1040-Y80R	1287 133	1411 047	25188 229	S 5010-Y30R	1287 664	206009 013				
25094 202	S 2060-G90Y	1287 568	1411 036	25094 212	S 2040-Y	1287 661	1411 048	25094 220	S 6010-R70B	1288 386	206009 030	25094 227	S 5010-B30G	1287 816	1411 056	25188 230	S 2502-Y	1287 716	206009 010				
25094 203	S 5005-G80Y	1287 361	1411 053	25094 213	S 3040-R20B	1287 656	1411 049	25094 221	S 5502-Y	1287 491	206009 006	25094 234	S 1505-Y40R	1287 069	206009 013	25188 231	S 5005-Y20R	1287 373	206009 013				
25094 204	S 4500-N	1287 742	206009 008	25094 214	S 4502-R	1287 382	1411 053	25094 222	S 3020-G70Y	1287 229	1411 053	25094 235	S 2000-N	1287 630	206009 009	25188 232	S 2010-Y20R	1292 855	1411 052				

■ **WESTERN EUROPE:** Austria: Tarkett Holding GmbH, Niederlassung Wien - Tel. +43 1 47 88 062 ■ Belgium: Tarkett Belux Sprl - Tel. +32 52 26 24 11 ■ Denmark: Tarkett A/S - Tel. +45 43 90 60 11 ■ Finland: Tarkett Oy - Tel. +358 9 4257 9000 ■ France: Tarkett SAS - Tel. +33 1 41 20 42 49 ■ Germany: Tarkett Holding GmbH - Tel. +49 62 33 810 ■ Greece: Tarkett Monoprosopi Ltd. - Tel. +30 210 6745 340 ■ Italy: Tarkett S.p.A. - Tel. +39 0744 7551 ■ Luxembourg: Tarkett GDL SA - Tel. +352 949 211 8804 ■ Netherlands: Tarkett BV - Tel. +31 416 685 491 ■ Norway: Tarkett AS - Tel. +47 32 20 92 00 ■ Portugal: Tarkett SA - Tel. +351 21 427 64 20 ■ Spain: Tarkett Floors S.L. - Tel. +34 914 951 400 ■ Sweden: Tarkett Sverige AB - Tel. +46 771 25 19 00 ■ Switzerland: Tarkett Holding GmbH - Tel. +41 043 233 79 24 ■ Turkey: Tarkett Turkey - Tel. +90 212 213 65 80 ■ United Kingdom: Tarkett Ltd. - Tel. +44 (0) 1622 854 040 ■ **EASTERN EUROPE:** Baltic Countries: Estonia: Tel. +372 55 515880 ■ Latvia: Tel. +371 26 112014 ■ Lithuania: Tel. +370 37 262220 ■ Czech Republic: Tarkett org. slozka - Tel. +420 271 001 600 ■ Hungary: Tarkett Polska Sp z o.o. magyarországi fióktelepe - Tel. +36 1 437 8150 ■ Kazakhstan: Tarkett Kazakhstan - Tel. +7 7172 79 00 99 ■ Poland: Tarkett Polska Sp. z o.o. - Tel. +48 22 16 09 231 ■ Russian Federation: ZAO Tarkett RUS - Tel. +7 495 775 3737 ■ Slovakia: Tarkett Polska, organizačná zložka - Tel. +421 2 48291 317 ■ **South East Europe:** Tarkett SEE - Tel. +381 21 7557 649 (44) 569 12 21 ■ **Ukraine:** Tarkett UA - Tel. +38 (0) 44 35 45 621 ■ **ASIA AND OCEANIA:** Australia: Tarkett Australia Pty Ltd. - Tel. +61 2 88 53 12 00 ■ China: Tarkett Floor Covering (Shanghai) Co. Ltd. - Tel. +86 (21) 60 95 68 38 ext 841 ■ **North East Asia:** Tarkett Hong Kong Limited - Tel. +852 2511 8716 ■ India: Tarkett Flooring India Pvt. Ltd. - Bangalore - Tel. +91 80 4130 3793 - New Delhi - Tel. +91 11 4352 4073 - Mumbai - Tel. +91 22 2648 8750 ■ **South East Asia:** Tarkett Flooring Singapore Pte. Ltd. - Tel. +65 6346 1585 ■ **AFRICA:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **MIDDLE EAST:** Tarkett Middle East: Tel. +961 1 51 3363/4 ■ Israel: Tarkett International: +33 1 41 20 41 01 ■ **NORTH AMERICA:** USA: Tarkett Inc. - Tel. +1 713 869 5811 / Johnsonite - Tel. +1 440 543 8916 ■ Canada: Tarkett Inc. - Tel. +1 450 293 173 ■ **LATIN AMERICA:** Brazil: Tarkett Brasil: Tel. 55 12 3954 7108 ■ Argentina - Chile - Uruguay: Tarkett Mercosur - Tel. +54 11 47 08 07 72 / +54 9 11 44 46 88 82 ■ Bolivia - Colombia - Ecuador - Panama - Paraguay - Peru - Trinidad and Tobago - Venezuela: Tarkett Latam - Tel. +55 11 9 8410 9310 / +55 11 95494 0069 ■ Mexico / Central America: Tarkett Mexico - Tel. +55 11 98410 9310





Essential: STAMP light turquoise 25094 211

DESIGN SPACES FOR UNCONDITIONAL COMFORT

Whether you are designing spaces in collective areas with traffic or comfortable places to relax in, Tarkett's Essential range is an ideal solution. Now available in NEW compact as well as acoustic version, the Essential collection offers 38 fresh and versatile decors in stone, wood and gentle print designs.

The Essential range is treated with Tarkett trademarked Top Clean XP™ surface protection for extreme durability and cost-effective maintenance. For maximum versatility, the collection is also available in modular format with Tapiflex Tiles 50 (50 x 50cm) or Tapiflex Planks 50 (100 x 25cm).



PHTHALATE
FREE



38 decors



MATTE
finish



Available in
Tapiflex Essential
(acoustic)
Acczent Essential
(compact)



**Residual indentation
to acoustic ratio**

Tapiflex Essential
(acoustic)

Acczent Essential
(compact)

0.10 mm* / 20 dB

0.02 mm* / 3 dB



Available in
rolls
tiles (50x50cm)
planks (100x25cm)

**Best measured value*



CHAMBRAY

green

LRV: 36.4%

25094 222

CHAMBRAY

anis

LRV: 52.3%

25094 217

STAMP

green

LRV: 37.4%

25094 202

STAMP

yellow

LRV: 46.6%

25094 212

STAMP

mastic

LRV: 47.2%

25094 205

CHAMBRAY

orange

LRV: 37.5%

25094 226

STAMP

orange

LRV: 30.4%

25094 207

STAMP

purple

LRV: 18.4%

25094 213



T: Tapiflex Essential (acoustic)
A: Acczent Essential (compact)



Available in tile (acoustic)

STAMP

LRV: 25.3%

kaki



T 25094 203

CHAMBRAY

LRV: 19.7%

dark aqua



T 25094 227

CHAMBRAY

LRV: 15.0%

dark denim



T 25094 220

STAMP

LRV: 15.2%

dark grey



T 25094 201

CHAMBRAY

LRV: 32.0%

denim




T 25094 224 / 25195 224

STAMP

LRV: 18.5%

petrol



T 25094 208

CHAMBRAY

LRV: 31.8%

aqua




T 25094 218

STAMP

LRV: 12.0%

dark blue



T 25094 200 / 25195 200 25184 200

STAMP

light turquoise LRV: 29.0%



T 25094 211



T: Tapiflex Essential (acoustic)
A: Acczent Essential (compact)



Available in tile (acoustic)

CHAMBRAY

grey beige
LRV: 47.9%



T 25094 223

SOFT STONE

warm grey
LRV: 50.0%



T 25094 236

25184 236

SOFT STONE

beige
LRV: 52.7%



T 25094 234

25184 234

CEMENT

light grey
LRV: 55.8%



T 25094 215

CEMENT

medium grey
LRV: 39.0%



T 25094 216 / **A** 25195 216

25184 216

STAMP

light grey
LRV: 26.5%



T 25094 204

CHAMBRAY

dark grey
LRV: 21.2%



T 25094 221

CEMENT

dark grey
LRV: 25.6%



T 25094 214

25184 214

CHAMBRAY

light grey
LRV: 37.6%



T 25094 225

SOFT STONE

cold grey
LRV: 51.6%



T 25094 235 / **A** 25195 235

25184 235