

# Tender Datasheet

# iD TILT HIT

## HETEROGENEOUS MODULAR VINYL

**Heterogeneous interlocking loose-lay vinyl flooring in tiles, with a total thickness of 6 mm, type iD TILT HIT.**

The floor covering is composed of an homogeneous wear layer of 2,70 mm thickness, reinforced with a double glass veil and is built on an agglomerated backing layer made of recycled vinyl flooring. It offers a **high dimensional stability  $\leq 0,10\%$**  according to EN ISO 23999 standard and a **high resistance to thermic dilatation**.

The product formulation does **not contain phthalate-based plasticizer**. It is built on a calendered backing layer made of recycled vinyl flooring material. It contains over 12% recycled material.

The product will be reinforced with a UV photocrosslinked polyurethane including particles of alumina TopClean XP™ treatment, highly resistant to abrasion,

scratches & stains, which permanently suppresses any wax and regenerating polish spray maintenance operations.

It will offer a high resistance to static indentation with an average value  $\leq 0.10$  mm according to EN SO 24343-1 standard.

The unique structure of the product will provide a **very high resistance to static & dynamic loads**.

According to DIN 51130 standard, the slip resistance of the floor covering will be classified **R10**, and according to EN 13501-1 standard, the floor covering will offer a fire resistance classified **B<sub>f</sub> s1**.

Its emission rate of volatile organic compounds in air will be very low, measured after 28 days according to EN standard 16516.

Close to zero emission (quantification limit), TVOC, TSVOC and formaldehyde emissions **will be below  $10 \mu\text{g}/\text{m}^3$** .

It will be free of formaldehyde and is 100% REACH compliant.

It will be **produced in Europe** & come with a **10 Year Warranty**.

It will be 100% recyclable and installation off-cuts can be collected and recycled in new products through the Tarkett ReStart® programme.



## More reasons to choose Tarkett iD TILT HIT

- + 100% Phthalate Free
- + No formaldehyde
- + 100% recyclable
- + Test reports and certificates available upon request
- + Optimal indoor air quality
- + TVOC  $\leq 10 \mu\text{g}/\text{m}^3$  after 28 days
- + FloorScore® certified
- + ISO 14001 certified production site
- + REACH Compliant and CE Marking